

NR500 Pro Series Industrial Cellular VPN Router

PRODUCT OVERVIEW

Industrial internet access

- Wireless Mobile Broadband 2G / 3G / 4G Connection
- Remote access to SCADA System for Industrial Automation
- Reduce high costs for on-site maintenance

Designed for industrial usage

- Power Input Range 9 to 48 VDC
- Industrial designed for harsh environment
- Compact metal casing for easy mounting

Secure and reliable remote connection

- Connection manager ensure seamless communication
- Support Multiple VPN tunnels for data encryption
- Firewall prevents unsafe and unauthorized access

Easy to use and easy maintenance

- User-friendly web interface for human interaction
- Easy configuration for deployment
- Support 3rd Party remote management cloud



TYPICAL APPLICATION



SPECIFICATION

CELLULAR	
Frequency Bands	4G(LTE) AU&NZ: B1/B2/B3/B4/B5/B7/B28, B40 EMEA: B1/B3/B5/B7/B8/B20, B38/B40/B41 America: B2/B4/B12/B13 Japan: B1/B3/B8/B18/B19/B26, B41 China: B1/B3/B8, B34/B38/B39/B40/B41 WCDMA: B1/B2/B4/B5/B8/B19 TD-SCDMA: B34/B39 GSM/EDGE: B2/B3/B5/B8 More Bands Demands please contact with us
SIM	2 x SIM slots, 1.8V / 3V
SIM Failover	Auto-switch cases: data limited, SMS limited, no network, network denied, data connection fail
Auto APN List	Operator APN list
Mobile Quota Control	Set up customized data limits for both SIM cards
Number of Antennas	2 (MAIN + AUX)
Connector	SMA female

ETHERNET	
Number of Ports	1 x WAN + 3 x LAN or 4 x LAN
Port Type	Auto 10/100 Mbps, auto MDI/MDIX
Magnet Isolation Protection	1.5 KV

Wi-Fi (Optional)	
Wireless Mode	IEEE 802.11b/g/n, Access Point (AP), Client
Wireless Speed	2*2 MIMO, 300 Mbps
Wireless Security	WPA, WPA2, WEP, CCMP, TKIP
Frequency Bands	2.412 - 2.484 GHz (2.4 GHz ISM band)
Antennas	2 x RP-SMA for Wi-Fi antenna connectors

SERIAL	
Number of Ports	1 x RS-232 (3 PIN) + 1 x RS-485
Connector	Terminal block
ESD Protection	± 15 KV
Baud Rate	300bps to 115200bps

DIGITAL INPUT & OUTPUT	
Type	2 x DI + 2 x DO
Connector	Terminal block
Isolation	3KVDC or 2KVrms
Absolute maximum VDC	36VDC
Absolute maximum ADC	100 mA

ORDERING INFORMATION

Model	Part Number	Description
NR500-P4G	A504433	4G LTE, Dual SIMs, 4 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC
	A514433	4G LTE, Dual SIMs, 4 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC, 2.4GHz Wi-Fi
NR500-P3G	A504333	3G, Dual SIMs, 4 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC
	A514333	3G, Dual SIMs, 4 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC, 2.4GHz Wi-Fi

NETWORK	
Routing	Static routing, Dynamic Routing(RIPv1/v2, OSPF, BGP)
Network Protocols	TCP, UDP, IPv4, ICMP, NTP, DNS, HTTP, HTTPS, ARP, VRRP, PPP, PPPoE, DHCP,
Connection Manager	Ping Detection, Timer Reboot, ICMP for link detection
DHCP	Static and dynamic IP allocation
DDNS	Supported some service providers, others can be configured manually
Network Backup	Cellular, Wired and Wi-Fi WAN options, each of which can be used as backup
Firewall	Flexible access control of TCP, UDP, ICMP packets, MAC address filter
SMS	SMS Configuration, SMS Gateway, SMS Notification

VPN	
OpenVPN	OpenVPN client, supports up to 5 x OpenVPN tunnels
IPsec	IKEv1, IKEv2, supports up to 5 x IPsec VPN tunnels
GRE	Layer2 and Layer3, supports up to 5 x GRE VPN tunnels
DMVPN	Dynamic Multipoint Virtual Private Networking DMVPN

MONITORING & MANAGEMENT	
Web GUI	HTTP/HTTPS, firmware upgrade
Command Line Interface	SSHv2 and TELNET
3 rd party platform	Exosite Cloud Platform
SNMP (Pending)	SNMP (v1, v2, v3), SNMP trap

POWER	
Connector	3-pin 3.5 mm female socket with lock
Input Voltage Range	9 to 48 VDC
Power Consumption	Idle: 100 mA@12 V Data link: 400 mA (peak) @12 V

HARDWARE SPECIFICATION	
Watchdog	Built-in watchdog
LEDs	SYS, NET, USR, RSSI x 3
Reset Button	Reset/restore to factory default button
Ingress Protection	IP30
Housing & Weight	Metal, 300 g
Dimensions	106mm x 106mm x 40mm
Installations	DIN-rail mounting
Operating Temperature	-40 °C to 75 °C
Operating Humidity	5% to 95% non-condensing

APPROVAL		
EMI	EN 55032:2012 Class B	
EMS	IEC 61000-4-2 ESD:	Level 4
	IEC 61000-4-3 RS:	Level 3
	IEC 61000-4-4 EFT:	Level 3
	IEC 61000-4-5 Surge:	Level 3
	IEC 61000-4-6 CS:	Level 3
Vibration	EN50155	